



Otani - F-33

Application: Agricultural
Brand: Otani
Pattern: F-33
Construction: Bias
Country of Origin: Thailand

AVAILABLE SIZES

RIM DIA	Size	Item #	Description	PR	TRA Code	Max Speed	Max Inflation Pressure	Max Load	Section Width	Overall DIA	Tread Depth
in						Mph	Psi	Lbs	in	in	32nds/in
16	7.50-16	316R	TT Tire Only	8	R 1	19	56	1918	8.66	32.13	25
16	8.00-16	380Z	TT Tire Only	4	R1/G1	25	23	1047	8.31	31.10	39
18	7.50-18	703T	TT Tire Only	8	R 1	19	59	1929	8.27	33.86	25
18	8.00-18	381B	TT Tire Only	6	R1/G1	25	34	1433	8.74	33.07	39
24	12.4-24	775F	TT Tire Only	8	R 1	25	32	3120	11.26	45.67	35
24	12.4-24	775E	TL Tire Only	8	R 1	25	36	3374	11.34	45.67	35
24	12.4-24	775R	TL Tire Only	12	R 1	25	44	3594	11.34	45.71	35
24	14.9-24	736B	TL Tire Only	6	R 1	19	20	3330	14.88	50.39	44
24	14.9-24	736E	TT Tire Only	8	R 1	19	26	3528	15.16	50.59	44
24	14.9-24	736P	TL Tire Only	12	R 1	19	38	4410	15.20	50.63	44
28	12.4/11-28	776F	TT Tire Only	8	R 1	19	26	3308	12	49.49	35
28	16.9-28	784M	TT Tire Only	10	R-1	19	28	4675	17	56.50	50
28	18.4-28	750A	TT Tire Only	8	R 1				17	58.50	58
30	16.9-30	793D	TT Tire Only	8	R 1	19	24	4950	17	58.39	58
30	16.9-30	793F	TT Tire Only	10	R 1	19	28	5413	17	58.50	58
30	18.4-30	795D	TT Tire Only	10	R 1	19	26	6207	19	60.83	58
30	18.4-30	795F	TT Tire Only	12	R 1	19	32	7012	19	60.94	58
34	18.4-34	814E	TT Tire Only	10	R 1	19	26	6538	19	63.11	58
34	18.4-34	814G	TT Tire Only	12	R 1				19	63.10	40