



Otani - G-45

Application: Off-Road/Industrial

Brand: Otani

Pattern: G-45

Construction: Bias

Country of Origin: Thailand

AVAILABLE SIZES

RIM DIA	Size	Item #	Description	PR	TRA Code	Max Speed	Max Inflation Pressure	Max Load	Section Width	Overall DIA	Tread Depth
in						Mph	Psi	Lbs	in	in	32nds/in
24	14.9-24	736C	TL Tire Only	10	R 4	25	36	6174	15.94	50.08	34
24	16.9-24	740F	TL Tire Only	10	R 4	25	32	6395	17.52	53.62	34
24	16.9-24	740J	TL Tire Only	12	R 4	25	38	7166	17.72	53.66	34
24	17.5L-24	744F	TL Tire Only	10	R 4	25	32	6174	17.95	51.57	34
24	17.5L-24	744M	TL Tire Only	12	R 4	25	36	6604	18.11	52.01	34
24	18.4-24	749C	TL Tire Only	10	R 4	25	28	7387	18.58	55.59	35
24	18.4-24	749F	TL Tire Only	12	R 4	25	36	8269	18.90	55.67	35
24	19.5L-24	751E	TL Tire Only	10	R 4	25	30	6615	19.49	51.65	34
24	19.5L-24	751I	TL Tire Only	12	R 4	25	34	7607	19.53	51.73	34
24	21L-24	752E	TL Tire Only	12	R 4	25	34	7601	21.97	55.51	35
28	16.9-28	784J	TL Tire Only	10	R 4	25	32	6780	16.93	55.31	34
28	16.9-28	784L	TL Tire Only	12	R 4	25	38	7607	17.01	55.51	34