



Otani - SA2100

Application: Passenger Car, Light Truck, Rough Terrain

Brand: Otani

Pattern: SA2100

Construction: Radial

Country of Origin: Thailand

AVAILABLE SIZES

RIM DIA	Size	Item #	Description	Load Index	Max Load	Max Inflation Pressure	Section Width	Overall DIA	Tread Depth	Uniform Tire Quality Grading		
in				Speed Symbol	Lbs	Psi	in	in	32nds/in	Traction	Temp	Treadwear
15	265/70R15	S211A	XL	116T	2756	50	10.75	29.49	12	640	A	A
17	265/70R17	S211J	XL	116T	2756	50	10.87	31.69	11	640	A	A
20	275/55R20	S212G	XL	117T	2833	50	10.98	31.93	11	640	A	A
20	275/60R20	S212K	XL	116T	2756	50	10.71	32.99	11	640	A	A

RIM DIA	Size	Item #	Description	PR	Load Index	Max Load Single	Max Load Double	Max Inflation Pressure	Section Width	Overall DIA	Tread Depth
in					Speed Symbol	Lbs		Psi	in	in	32nds/in
15	31x10.50R15LT	S140C	109S	6	109S	2270	-	50	10.55	30.43	15
17	33x12.50R17LT	S141D	120Q	10	120Q	3085	-	65	12.60	32.48	18
17	35x12.50R17LT	S142D	121Q	10	121Q	3195	-	65	13.11	34.49	18
17	LT285/70R17	S151B	121/118S	10	121/118S	3195	2910	80	11.54	32.72	15
18	33x12.50R18LT	S141F	118Q	10	118Q	2910	-	65	12.44	32.48	18
18	35x12.50R18LT	S142F	123Q	10	123Q	3415	-	65	12.80	34.45	18
18	LT275/65R18	S149D	123/120S	10	123/120S	3415	3085	80	10.63	32.09	16
18	LT275/70R18	S149N	125/122S	10	125/122S	3640	3305	80	10.71	33.19	16
20	33x12.50R20LT	S141J	119Q	12	119Q	3000	-	80	12.28	32.52	19
20	35x12.50R20LT	S142J	125Q	12	125Q	3640	-	80	12.44	34.49	18
20	LT275/65R20	S149I	126/123S	10	126/123S	3750	3415	80	10.91	34.13	16
20	LT285/55R20	S150B	122/119S	10	122/119S	3305	3000	80	11.38	32.40	15
20	LT285/60R20	S150E	125/122S	10	125/122S	3640	3305	80	11.38	33.39	15